Dino-Lite Europe - Phone: - Email:

## **AM7013MT**

**Brand:** Dino-Lite

**Product Code:** AM7013MT




## **Short Description**

5 Megapixel resolution Robust metal housing 10-70x & 200x Magnification Great choice for generic applications

## **Description**

The Dino-Lite AM7013MT has a 5 megapixel sensor for crystal clear images, even under higher magnification. Because of the very high resolution, the AM7013MT is the ideal solution for displaying microscopic images on large screens or using the microscopic images for printing.



Working distance/field of view/depth of field				
WORKING	FIELD OF	FIELD OF	DEPTH OF	
DISTANCE	VIEW(X)	VIEW(Y)	FIELD	
			Unit = mm	
48.7	19.8	14.9	3.6	
21.7	13.2	9.9	1.9	
9.0	9.9	7.4	-	
1.9	7.9	5.9	0.88	
-2.3	6.6	5.0	-	
-0.1	1.8	1.4	0.20	
1.0	1.7	1.3	-	
2.1	1.7	1.2	-	
	WORKING DISTANCE 48.7 21.7 9.0 1.9 -2.3 -0.1	WORKING FIELD OF VIEW(X)  48.7 19.8 21.7 13.2 9.0 9.9 1.9 7.9 -2.3 6.6 -0.1 1.8 1.0 1.7	WORKING FIELD OF VIEW(X)  48.7	

Specification

Specification	
Lighting	
Light/ LED type	White
Number of LEDs	8
LED on/off switchable:	Yes
Infrared filter	IR cut-filter >650 nm
Diffuser available	No
Emission filter	No
Polarizer	No
Optics	
Magnification	10-70x, 200x
Macro zoom	No
Working distance	Standard
Lens type	Glass with anti-reflection coating
Sensor	
Sensor type	CMOS
Resolution	5 Megapixel (2592x1944)
Maximum frame rate	30 fps
Compatibility	
Interface	USB 2.0
Operating system	Windows 7, 8, 10 & 11, MacOS 10.9 and up
Included software	DinoCapture 2.0 (Windows), DinoXcope (Mac
	OS)
Supported image formats	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA,
(Windows)	PCX, MNG, WBMP, JP2, JPC, PGX
Supported video formats	WMV, FLV, SWF
(Windows)	

Supported image formats (MacOS)	JPEG, PNG
Supported video formats (MacOS)	MOV (max 1.3MP)
Imaging standards	DirectShow, UVC
Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)
Housing	(optional)
Housing material	Metal housing
Magnification lock	No
Dimensions	10.5cm (L) x 3.2cm (D)
Weight	140g
Cable length	1.8m
Features	
Special feature	No
Measurement	Yes
Calibration	Yes
Microtouch sensor	Yes
ESD safe	Yes
Information	
Package contents	Microscope, Carry pouch, software CD, calibration
	target, user manual
Warranty information	2 years European warranty
Regulatory approval	CE, FCC, ROHS
Price range	€600,00 - €800,00

## Price range Product Gallery