Dino-Lite Europe - Phone: - Email:

# **AM4917MZT4**



Marke:

**Artikelnummer:** AM4917MZT4

### **Short Description**

1.3 Megapixels
Extended Depth of Field (EDOF)
Extended Dynamic Range (EDR)
Automatic Magnification Reading (AMR)
Enhanced Flexible LED Control (eFLC)

#### **Beschreibung**

As magnification increases, targets with uneven surfaces are often out of focus due to the limited depth of field. AM4917MZT4 400x digital microscope eases focusing with its click-to-focus functionality and can generate focused-stacked images with EDOF. Delivering superior images, equipped with a polarizer, and featuring EDOF, DPQ, AMR, and EDR, AM4917MZT4 is a quality imaging tool ready for a wide range of applications.

Note: EDOF, EDR, and DPQ are available on Windows PC only.





















#### The main features of the AM4917MT8 are:

- 1.3 Megapixels
- Extended Depth of Field (EDOF)
- Extended Dynamic Range (EDR)
- Automatic Magnification Reading (AMR)
- Enhanced Flexible LED Control (eFLC)
- Integrated polarizer (anti-reflection)
- 400x-470x magnification
- And more...

### (\*EDOF/EDR only functions under Windows OS)

## **Optical Data Table**

| <b>MAGNIFICAT</b> | TWORKING          | FIELD OF     | FIELD OF | <b>DEPTH OF</b> |
|-------------------|-------------------|--------------|----------|-----------------|
| ON RATE           | <b>DISTANCE</b> * | VIEW(X)      | VIEW(Y)  | FIELD           |
| 400               | 5.68              | 0.977        | 0.732    | 0.041           |
| 410               | 6.63              | 0.953        | 0.715    | 0.040           |
| 420               | 7.59              | 0.93         | 0.698    | 0.039           |
| 430               | 8.55              | 0.909        | 0.681    | 0.038           |
| 440               | 9.51              | 0.888        | 0.666    | 0.038           |
| 450               | 9.62              | 0.868        | 0.651    | 0.037           |
| 460               | 9.56              | 0.849        | 0.637    | 0.036           |
| 470               | 9.50              | 0.831        | 0.623    | 0.036           |
| T • 4 1 1         | 1.66 1.141        | * TT7041 4 C | 4        | TT •4           |

Listed values may differ slightly \* Without front

Unit = mm

cap

# **Spezifikation**

| ~ <u>r · </u>   |       |  |
|-----------------|-------|--|
| Lighting        |       |  |
| Light/ LED type | White |  |
| Number of LEDs  | 8     |  |

| Optics                  |  |  |  |  |  |
|-------------------------|--|--|--|--|--|
| Magnification           | $400x \sim 470x$                             |  |  |  |  |
| Sensor                  |  |  |  |  |  |
| Sensor type             | CMOS   |  |  |  |  |
| Resolution              | 1.3 Megapixel (1280x960)                     |  |  |  |  |
| Maximum frame rate      | 30 fps in 1.3 MP, MJPEG 30 fps in VGA, MJPEG |  |  |  |  |
| Compatibility           |  |  |  |  |  |
| Interface               | USB 2.0                                      |  |  |  |  |
| Operating system        | Windows 7, 8, 10 & 11, MacOS 10.12 and up    |  |  |  |  |
| Software                | DinoCapture 2.0 (Windows), DinoXcope (Mac    |  |  |  |  |
|                         | OS)  |  |  |  |  |
| Supported image formats | BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP,     |  |  |  |  |
| (Windows)               | JP2, JPC, JPG, PGX, RAS, PNM                 |  |  |  |  |
| Supported video formats | WMV, FLV, SWF                                |  |  |  |  |
| (Windows)               |  |  |  |  |  |
| Supported image formats | PNG, JPEG                                    |  |  |  |  |
| (MacOS)                 |  |  |  |  |  |
| Supported video formats | MOV  |  |  |  |  |
| (MacOS)                 |  |  |  |  |  |
| Housing                 |  |  |  |  |  |
| Housing material        | Metal housing                                |  |  |  |  |
| Dimensions              | 10.7 cm (H) x 3.3 cm (D)                     |  |  |  |  |
| Weight                  | 130 g  |  |  |  |  |
| Features                |  |  |  |  |  |
| Measurement             | Yes  |  |  |  |  |
| Calibration             | Yes  |  |  |  |  |
| Microtouch sensor       | Yes  |  |  |  |  |
| Information             |  |  |  |  |  |
| Warranty information    | 2 years European warranty                    |  |  |  |  |
| Regulatory approval     | CE, FCC, ROHS                                |  |  |  |  |
| Price range             | €1200,00 - €1400,00                          |  |  |  |  |