

# AM7013MZT4

**Brand:** Dino-Lite  
**Product Code:** AM7013MZT4











## Short Description

5 Megapixel resolution  
Robust metal housing  
400-470x magnification  
Polarizer (anti-reflection)

## Description

The Dino-Lite AM7013MZT4 has a 5 megapixel sensor for crystal clear images. With its high magnification of 400~470x, it reveals even the smallest details on all kinds of objects. The built-in adjustable polarizer reduces glare and reflection on shiny objects.

---

	USB 2.0		Measurement functionality		Adjustable ~400x -470x
	5 megapixel 2592 x 1944		8 White LEDs switchable		Metal housing
	Standard working distance		Polarizer anti-reflection		

---

Because of the very high resolution, the AM7013MZT4 is the ideal solution for displaying microscopic images on large screens or using the microscopic images for

printing.

### Working distance/field of view/depth of field

MAGNIFICATION RATE	WORKING DISTANCE	FIELD OF VIEW(X)	FIELD OF VIEW(Y)	DEPTH OF FIELD
<b>Listed values may differ slightly</b>				<b>Unit = mm</b>
430	-0.45	0.92	0.69	0.1
440	0.4	0.9	0.67	0.1
450	1.35	0.88	0.66	0.1
460	2.3	0.86	0.65	0.1
470	3.15	0.84	0.63	0.1

### Specification

Lighting	
Light/ LED type	White
Number of LEDs	8
LED on/off switchable:	Yes
Infrared filter	IR cut-filter >650 nm
Diffuser available	No
Emission filter	No
Polarizer	Yes, linear
Optics	
Magnification	400-470x
Macro zoom	No
Working distance	Standard
Lens type	Glass with anti-reflection coating
Sensor	
Sensor type	CMOS
Resolution	5 Megapixel (2592x1944)
Maximum frame rate	30 fps
Compatibility	
Interface	USB 2.0
Operating system	Windows 7,8,10 & 11, MacOS 10.9 and up
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)

Supported image formats (Windows)	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX
Supported video formats (Windows)	WMV, FLV, SWF
Supported image formats (MacOS)	JPEG, PNG
Supported video formats (MacOS)	MOV (max 1.3MP)
Imaging standards	DirectShow, UVC
Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)
<b>Housing</b>	
Housing material	Metal housing
Magnification lock	No
Dimensions	10.5cm (L) x 3.2cm (D)
Weight	140g
Cable length	1.8m
<b>Features</b>	
Special feature	No
Measurement	Yes
Calibration	Yes
Microtouch sensor	Yes
ESD safe	Yes
<b>Information</b>	
Package contents	Microscope, carry pouch, software CD, calibration target, ZT-Z-CC1 cap closure, user manual
Warranty information	2 years European warranty
Regulatory approval	CE, FCC, ROHS
Price range	€700,00 - €900,00

## Product Gallery

