Dino-Lite Europe - Phone: - Email:

## AD7013MTL

**Brand:** Dino-Lite

**Product Code:** AD7013MTL



#### **Short Description**

5 Megapixel resolution Long working distance 20-90x magnification Robust metal housing Exchangeable caps

### **Description**

The Dino-Lite AD7013MTL has a 5 megapixel sensor for crystal clear images, even under higher magnification. Because of the very high resolution, the AD7013MTL is the ideal solution for displaying microscopic images on large screens or using the microscopic images for printing.



**USB 2.0** 





Continuous ~20x-90x



5 megapixel 2592 x 1944



8 White LEDs switchable



Metal housing





The AD series are equipped with exchangeable caps for even more flexibility. The long working distance of up to 15 cm enables the possibility to work under the microscope.

### Working distance/field of view/depth of field

	O		1		
M	IAGNIFICATI	WORKING	FIELD OF	FIELD OF	DEPTH OF
O	N RATE	DISTANCE	VIEW(X)	VIEW(Y)	FIELD
Listed values					Unit = mm
m	ay differ				
sl	ightly				
20	)	160.5	19.8	14.9	6
30	)	110.4	13.2	9.9	3.4
4(	)	86.7	9.9	7.4	2.2
50	)	73.6	7.9	5.9	1.65
60	)	65.7	6.6	5.0	-
70	)	60.8	5.7	4.2	-
80	)	57.8	5.0	3.7	-
9(	)	56.1	4.4	3.3	0.8

### **Specification**

Specification				
Lighting				
Light/ LED type	White			
Number of LEDs	8			
LED on/off switchable:	Yes			
Infrared filter	IR cut-filter >650 nm			
Diffuser available	No			
Emission filter	No			
Polarizer	No			
Optics				
Magnification	20-90x			
Macro zoom	No			
Working distance	Long			
Lens type	Glass with anti-reflection coating			
Sensor	ensor			
Sensor type	CMOS			
Resolution	5 Megapixel (2592x1944)			
Maximum frame rate	30 fps			
Compatibility				

Interface	USB 2.0		
Operating system	Windows 7,8,10 & 11, MacOS 10.9 and up		
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)		
Supported image formats (Windows)	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX		
Supported video formats (Windows)	WMV, FLV, SWF		
Supported image formats (MacOS)	JPEG, PNG		
Supported video formats (MacOS)	MOV (max. 1.3MP)		
Imaging standards	DirectShow, UVC		
Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)		
Housing			
Housing material	Metal housing		
Magnification lock	No		
Dimensions	10.5cm (L) x 3.2cm (D)		
Weight	140g		
Cable length	1.8m		
Features			
Special feature	No		
Measurement	Yes		
Calibration	Yes		
Microtouch sensor	Yes		
ESD safe	Yes		
Information			
Package contents	Microscope, carry pouch, open and closed cap, software CD, calibration target, user manual		
Warranty information	2 years European warranty		
Regulatory approval	CE, FCC, ROHS		
Price range	€600,00 - €800,00		

# **Product Gallery**

