Dino-Lite Europe - Phone: - Email:

AM8117MZTL



Marque:

Code produit: AM8117MZTL Edge Plus

Courte description

High Optical Resolution 8.0 Megapixel Enhanced Flexible LED Control (eFLC) Long Working Distance Robust Metal Housing

Description

The AM8117MZTL 8-megapixel long working distance digital microscope captures images with stunning clarity and sharpness. Its advanced sensor technology, combined with the eFLC feature and adjustable polarizer, make the AM8117MZTL a reliable tool for high-quality imaging,



Metal housing



Enhanced Flexible LED control



Adjustable ~10x-140x



8,0 Megapixels 3840 x 2160





8 White LEDs switchable





The main features of the AM8117MZTL are:

- 8 Megapixels
- High Optical Resolution
- Enhanced Flexible LED Control (eFLC)
- Long Working Distance (LWD) Optics
- Adjustable Polarizer
- Robust Metal Housing
- $10x \sim 140x$ magnification (Edge shading occurs below 25x when previewing in 16:9 windows.)
- And more...

Working distance/field of view/depth of field

MAGNIFICAT	I WORKING	FIELD OF	FIELD OF	DEPTH OF
ON RATE	DISTANCE *	VIEW(X)	VIEW(Y)	FIELD
10	238.3	60.69	34.14	25.99
20	115.4	30.35	17.07	6.94
30	75.9	20.23	11.38	3.29
40	57.1	15.17	8.53	1.98
50	46.7	12.14	6.83	1.35
60	40.5	10.11	5.69	0.99
70	36.7	8.67	4.88	0.77
80	34.3	7.59	4.27	0.62
90	32.9	6.74	3.79	0.52
100	32.3	6.07	3.41	0.44
110	32.1	5.52	3.10	0.38
120	32.3	5.06	2.85	0.33
130	32.8	4.67	2.63	0.30
140	33.5	4.34	2.44	0.27
Listed volues m	ov diffor cliabtly	* Without front		Unit – mm

Listed values may differ slightly * Without front

Unit = mm

cap

Spécification

Lighting	
Light/ LED type	White
Number of LEDs	8
Optics	

N	10 140			
Magnification	$10x \sim 140x$			
Working distance	238.3 ~ 33.5 mm			
Sensor				
Sensor type	CMOS			
Resolution	8.0 Megapixel (3840x2160)			
Maximum frame rate	10 fps at 8.0 MP, MJPEG 25 fps at 2.0 MP,			
	MJPEG			
Compatibility				
Interface	USB 2.0			
Operating system	Windows 10/11			
Supported image formats	BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP,			
(Windows)	JP2, JPC, JPG, PGX, RAS, PNM			
Supported video formats	WMV, FLV, SWF			
(Windows)				
Housing				
Housing material	Metal housing			
Dimensions	130 mm (H) x 33 mm (D)			
Weight	120 g			
Features				
Special feature	Auto and Manual Refocus			
Measurement	Yes			
Calibration	Yes			
Microtouch sensor	Yes			
Information				
Package contents	N3C-C (Close Cap) N3C-D (Diffuser Cap) N3C-			
	D2 (Opal Diffuser Cap) N3C-E (Extended Open			
	Cap) N3C-L (Long Cap) N3C-O (Open Cap) N3C-			
	S (Sidelight Cap)			
Warranty information	2 years European warranty			
Regulatory approval:	CE, FCC, ROHS			
Price range	€1149,00 - €1349,00			