AM4113TL




Marque: Code produit: AM4113TL

Courte description

1.3 Megapixel resolutionWith magnification lock10x ~ 90x magnificationLong working distance

Description

The AM4113TL is a special model with long working distance up to 15 cm at 20x magnification and around 4cm at 90x magnification. The extra working distance makes the TL series an ideal solution for tasks where you need more working distance to the object, for example repair, rework or assembly tasks.



Working distance/field of view/depth of field

MAGNIFICATI WORKING		FIELD OF	FIELD OF	DEPTH OF	
ON RATE	DISTANCE	VIEW(X)	VIEW(Y)	FIELD	
20	151.0	19.6	15.6		6
30	101.0	13.0	10.4	3.4	
40	77.2	9.8	7.8	2.2	
50	64.1	7.8	6.3	1.65	
60	56.2	6.5	5.2	•	
70	51.3	5.6	4.5		
80	48.3	4.9	3.9	•	
90	46.6	4.3	3.5	0.8	
Listed values				Unit = mm	
may differ					
slightly					

Spécification		
Lighting		
Light/ LED type	White	
Number of LEDs	8	
LED on/off switchable:	Yes	
Infrared filter	IR cut-filter >650 nm	
Diffuser available	No	
Emission filter	No	
Polarizer	No	
Optics		
Magnification	10x ~ 90x	
Macro zoom	No	
Working distance	Long	
Lens type	Glass with anti-reflection coating	
Sensor		
Sensor type	CMOS	
Resolution	1.3 Megapixel (1280x1024)	
Maximum frame rate	30 fps	
Compatibility		
Interface	USB 2.0	
Operating system	Windows 7, 8, 10 & 11, MacOS 10.9 and up	
Software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)	
Supported image formats (Windows)	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX	
Supported video formats (Windows)	WMV, FLV, SWF	

Supported image formats (MacOS)	JPEG, PNG		
Supported video formats (MacOS)	MOV		
Imaging standards	DirectShow, UVC		
Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)		
Housing			
Housing material	Composite/ plastic housing		
Magnification lock	Yes		
Dimensions	10.5cm (L) x 3.2cm (D)		
Weight	105g		
Features			
Special feature	No		
Measurement	Yes		
Calibration	Yes		
Microtouch sensor	Yes		
ESD safe	No		
Information			
Package contents	Microscope, carry pouch, software CD, calibration target, user manual		
Warranty information	2 years European warranty		
Regulatory approval	CE, FCC, ROHS		
Price range	€350,00 - €500,00		