Dino-Lite Europe - Phone: - Email:

AM7515MT1A



Marque: Dino-Lite

Code produit: AM7515MT1A

Courte description

5 Megapixel resolution 70-140x magnification Coaxial and brightfield illumination Flexible LED Control (FLC) Automatic Magnification Reading (AMR)

Description

The AM7515MT1A is a 5MP Dino-Lite Edge Series microscope that has a magnification range of 70-140x with built-in coaxial illumination. By using the Flexible LED Control (FLC), this model is capable of switching between or mixing, brightfield and coaxial illumination.



USB 2.0





Adjustable ~70x-140x



Standard working distance





Automatic Magnification Reading (AMR)







The coaxial illumination technique reveals details that are very difficult to see under normal light. The AM7515MT1A includes the Automatic Magnification Reading (AMR) feature which automatically detects and displays the magnification in the included Dino-Lite software. These unique features make the Dino-Lite AM7515MT1A a great inspection tool for material analysis, electronics inspection, or any similar application that requires, coaxial illumination, versatility and mobility. The Dino-Lite AM7515MT1A is bundled with the user-friendly DinoCapture 2.0 software for Windows.

For this model it includes functions such as:

- Automatic Magnification Reading (AMR)
- Flexible LED Control (FLC)
- Calibration
- Measurement
- Capturing & annotating images
- And recording video

Working distance/field of view/depth of field

MAGNIFICATI	WORKING	FIELD OF	FIELD OF	DEPTH OF
ON RATE	DISTANCE*	VIEW(X)	VIEW(Y)	FIELD
70	38.6	5.6	4.2	0.77
80	36.2	4.9	3.7	0.62
90	34.8	4.3	3.3	0.52
100	34.2	3.9	2.9	0.44
110	34.0	3.6	2.7	0.38

120	34.2	3.3	2.4	0.33
130	34.7	3.0	2.3	0.30
140	35.4	2.0	2.1	0.27
Listed values	*Without front		Unit = mm	
may differ	cap			
slightly				

Spécification

Lighting			
Light/ LED type	White		
Number of LEDs	8		
LED on/off switchable:	Yes		
Infrared filter	IR cut-filter >650 nm		
Diffuser available	Yes, N3C-D		
Emission filter	No		
Polarizer	No		
Optics			
Magnification	70-140x		
Macro zoom	No		
Working distance	Standard		
Lens type	Glass with anti-reflection coating		
Sensor			
Sensor type	CMOS		
Resolution	5 Megapixel (2592x1944)		
Maximum frame rate	30fps (max 20fps video recording)		
Compatibility			
Interface	USB 2.0		
Operating system	Windows 7, 8, 10 & 11, MacOS 10.11.16 and up		
Included software	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)		
Supported image formats	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA,		
(Windows)	PCX, MNG, WBMP, JP2, JPC, PGX		
Supported video formats	WMV, FLV, SWF		
(Windows)			
Supported image formats	JPEG, PNG		
(MacOS)			
Supported video formats	MOV (max 1.3MP)		
(MacOS)			
Imaging standards	DirectShow, UVC		

Wifi	Wireless-ready, requires the WF-10 WiFi streamer (optional)		
Housing			
Housing material	Metal housing		
Magnification lock	Yes		
Dimensions	10.5cm (L) x 3.2cm (D)		
Weight	140g		
Cable length	1.8m		
Features			
Special feature	Automatic Magnification Reading (AMR),		
	Flexible LED Control (FLC), Coaxial illumination		
Measurement	Yes		
Calibration	Yes		
Microtouch sensor	Yes		
ESD safe	Yes		
Information			
Package contents	Microscope, carry pouch, software CD, user		
	manual, quick guide, calibration target, front cover		
	box		
Warranty information	2 years European warranty		
Regulatory approval	CE, FCC, ROHS		
Price range	€1000,00 - €1200,00		

Galerie du produit